

间距 (space) :1.25mm



耐压 (Withstand voltage) : 500V AC/minute

型号 Type	适用导线范围 Wire Range		导线外径 Wire ins.Dis
	mm ²	AWG#	
CH-TJC1257	0.08~0.032	28~32	0.9~0.5
材质·表面处理 Material and Finish			
磷青铜 镀金 Phos·bronze Gold·Plated			

The technical drawings show two views of the sprocket assembly:

- Top View:** A plan view showing the sprocket teeth and the mounting flange. Dimensions include:
 - A:** Total width of the sprocket.
 - B:** Width between the mounting flanges.
 - C:** Total length of the sprocket body.
 - D:** Distance from the centerline to the outer edge of the mounting flange.
 - E:** Thickness of the mounting flange.
 - F:** Distance from the centerline to the start of the teeth.
 - G:** Pitch diameter of the sprocket.
 - H:** Addendum circle diameter.
 - I:** Root circle diameter.
 - J:** Keyway width.
 - K:** Key height.
 - L:** Key depth.
 - M:** Key length.
- Side View:** A cross-sectional view showing the sprocket teeth and the mounting flange. Dimensions include:
 - N:** Total thickness of the sprocket.
 - O:** Thickness of the mounting flange.
 - P:** Distance from the centerline to the outer edge of the mounting flange.
 - Q:** Distance from the centerline to the start of the teeth.
 - R:** Pitch diameter of the sprocket.
 - S:** Addendum circle diameter.
 - T:** Root circle diameter.
 - U:** Keyway width.
 - V:** Key height.
 - W:** Key depth.
 - X:** Key length.

线数 Poles	型号 Type	尺寸Dimensions (mm)			线数 Poles	型号 Type	尺寸Dimensions (mm)		
		A	B	C			A	B	C
13	TJC1257-13Y	11.00	7.50	9.90	21	TJC1257-21Y	16.00	12.50	14.90
15	TJC1257-15Y	12.25	8.75	11.15	31	TJC1257-31Y	22.25	18.75	21.15
17	TJC1257-17Y	13.50	10.00	12.40	41	TJC1257-41Y	28.50	25.00	27.40
19	TJC1257-19Y	14.75	11.25	13.65					
材质 Material PA66 UL94V-0									